

CONTEGA SOLIDO EXO-D

Full-surface adhesive window sealing tape for exterior use with an additional adhesive zone on the fleece side



Technical data

Substance		
Backing	PP backing fleece, PP copolymer special membrane	
Adhesive	modified waterproof SOLID adhesive / special acrylate adhesive	
Release film	one or two split silicone-coated PE sheet	
Attribute	Regulation	Value
Colour		black
sd-value	BS EN 1931	0.7 m
g-value		3.5 MNs/g
Exposure time		3 months
Water column	BS EN 20811	> 2 500 mm
Can be plastered over		yes
ift Rosenheim (DE) testet	MO-01/1:2007-01, Abs. 5	passed, circumferential
Application temperature		above -10 °C ; 14 °F
Temperature resistance		permanent -40 °C to 90 °C ; -40 °F to 194 °F
Storage		cool and dry

Area of application

The CONTEGA SOLIDO EXO-D joint adhesive tape, which is full-surface adhesive and can be plastered over, ensures windtight and diffusion-permeable exterior sealing of windows and doors to adjacent building components made of wood and mineral subsurfaces such as concrete and masonry.

The integrated adhesive zone on the fleece side allows for easy adhesion to windows and doors.

The stuck joint is immediately windproof and can be subjected to loading. The fleece can simply be plastered over in accordance with our application guide.

Forms of delivery

Art. no.	GTIN	Length	Width	Weight	PU	Container
16135	4026639161352	30 m	80 mm	0.9 kg	8	288
16136	4026639161369	30 m	100 mm	1.1 kg	8	288

Advantages

- ✓ Full-surface adhesive, the joint is immediately windproof and resistant to driving rain, and it can be subjected to loading
- ✓ Extremely strong adhesion on mineral subsurfaces too thanks to modified waterproof SOLID adhesive
- ✓ Can be plastered over
- ✓ The integrated adhesive zone on the fleece side makes it easy to seal joints to windows and doors
- ✓ Easy to apply

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact
Ireland
T. 046 9432104
F. 046 9432435
UK
T. 01228 711 511
F. 01228 712 280

Ecological Building Systems
info@ecologicalbuildingsystems.com

www.ecologicalbuildingsystems.com



Substrates

Before sticking, subsurfaces should be brushed off, wiped clean with a cloth or cleaned using compressed air.

Uneven mineral subsurfaces may need to be levelled with a smooth finish.

Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded.

Subsurfaces must be sufficiently dry and have sufficient load-bearing capacity.

Permanent adhesion is achieved on all pro clima exterior membranes and on other underlay/sarking and wall lining membranes (e.g. those made of PP and PET).

Adhesion can be carried out on planed and painted wood, hard plastics, hard wood-based panels (chipboard, OSB and plywood panels) and on mineral subsurfaces such as concrete and masonry.

The best results in terms of structural stability are achieved on high-quality subsurfaces.

It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases.


Pretreatment with TESCON PRIMER RP is recommended in the case of subsurfaces with insufficient load-bearing capacity.

General conditions

The bonds should not be subjected to tensile strain.

Press firmly to secure the adhesive tapes, taking care to ensure that there is sufficient resistance pressure behind them.

Driving rainproof and windtight seals can only be achieved if this connection tape is laid without folds or creases and are uninterrupted.



Prüfbericht Nr. 15-003305-PRO1
(PB-E03-020310-de-02)
• CONTEGA SOLIDO SL-D
• CONTEGA SOLIDO EXO-D
nach MO-01/1:2007-01, Abs. 5
15.03.2016

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact
Ireland
T. 046 9432104
F. 046 9432435
UK
T. 01228 711 511
F. 01228 712 280

Ecological Building Systems
info@ecologicalbuildingsystems.com

www.ecologicalbuildingsystems.com

