




TESCON® SPRIMER

Sprayable primer

Wash primer for wood, wood-fibre boards, masonry, roofs, walls and ground slabs for subsequent adhesion with pro clima adhesive tapes such as TESCO VANA, TESCO PROTECT and the EXTONSEAL range.

Advantages

- ✓ Easy to apply - spray on directly from the can, no contamination of the primer in its container
- ✓ Secure bonds: penetrates deep and strengthens dusty subsurfaces or subsurfaces with insufficient load-bearing capacity
- ✓ Saves time: adhesive tapes can be stuck to absorbent subsurfaces with no drying time
- ✓ Flexible use: use on dry and slightly moist subsurfaces
- ✓ At any time of the year: can also be applied during frosty conditions



www.proclima.com

... and the insulation
is perfect





Technical data

Substance	
Material	Synthetic rubber
Attribute	
Value	
Colour	translucent
Application temperature	23 °F to 104 °F ; -5 °C to +40 °C
Temperature resistance	permanent 23 °F to ~195 °F, short-term up to 212 °F (1 h); °C: -5 to ~90; 100
Storage	protect from frost, cool and dry

Forms of delivery

Art. no.	GTIN	Content	Adhesive tape width	Coverage	PU	PU/pallet
1AR01114	4026639211149	13.5 oz (400 ml)	2 3/8" (60 mm)	~22 yd (20 m)	12	84
			3" (75 mm)	~18.5 yd (17 m)		
			6" (150 mm)	~10 yd (9 m)		
1AR01050	4026639210500	25.4 oz (750 ml)	2 3/8" (60 mm)	~41 yd (38 m)	6	56
			3" (75 mm)	~34 yd (31 m)		
			6" (150 mm)	~18.5 yd (17 m)		

Application Guide



1 Preparing the subsurface

Brush off or wipe down the subsurface, if necessary.



2 Preparing the can of primer

Shake the can vigorously for at least 20 seconds.



3 Applying the primer

Spray TESCO SPRIMER from a distance of approx. 20 cm to the surface to form a seamless coating.



4 Turning the jet direction

The spray jet can be adjusted in the vertical or horizontal directions to suit the application situation.



5 Sticking

The pro clima adhesive tapes TESCO or CONTEGA, for example, can be stuck onto surfaces treated with primer without any waiting period.



6 Final adhesive strength

The adhesive joint achieves its high final level of strength once the primer has dried fully.

Further information about application and construction is given in the pro clima planning documentation and application recommendations.

(Please also note the recommendations of the currently valid version of the pro clima application matrix.)

For Stockists contact:

Ireland: ☎ 046 9432104, 📠 046 9432435

UK: ☎ 01228 711511, 📠 01228 712280

info@ecologicalbuildingsystems.com

MOLL

bauökologische Produkte GmbH

Rheintalstraße 35 - 43

D-68723 Schwetzingen

Fon: +49 (0) 62 02 - 27 82.0

eMail: info@proclima.info

www.proclima.com

