

Product Description Access Hatch



■ Access hatch with thermal protection WS3D and BD

■ Dimension (size of the ceiling opening in cm)

	Standard Size
Length	60
Width	60
Hight	8,5

The finished measurement of the casing is 1.5 cm smaller in both width and length than the ceiling opening.

■ Casing

18 mm MultifunctionBoard, foil-coated, white, EN 13986-P5

■ Trapdoor

16 mm chipboard, melanine resin-coated, white, circumferential ABS furniture edging, smooth surface due to covered quality hinges

■ hoka twin-wall-sealing

TPV-profile with two degrees of hardening, lift range of sealing 4 mm, resistant against temperature / environmental influences and ageing

■ Quality hinges

Mechanics: Automatic hinges with clipping technology, trapdoor is completely pressed to twin-wall-sealing
Function: Simple adjustment (length, width, depth) of the trapdoor for optimum, tight closing; door can be quickly removed / fitted for more simple installation or when placing bulky items, enables to clad the door up to 6 mm thickness and a weight up to 10 kg/m²

■ Architraves

Plastic, white, special profile 40x6 mm, preassembled adhesive tape, plug-in system with corner joints

Delivered with complete installation kit and push / pull rod.

■ Thermal protection WS3D

Material: Insulation 32 mm polyethylene-thermodeck, airtight sealing system for the gap between ceiling and casing: double faced adhesive tape and insulation braid

Testresults: Tested as complete constructional element:
 Insulation U=1,0 (DIN EN ISO 12567)
 Airtight sealing system a=0,02 (DIN EN 1026)
 Incl. WS installation kit (contains all the required materials) and the certified sealing system for airtight installation

■ Blower-Door

Magnetic catch (2x) with 5kg retention force, additional lock, blower-door-test suited a=0,04 (DIN EN 1026)



wellhöfer
 TREPPEN AUS WÜRZBURG